

TRANSMITTAL LETTER TO THE UNITED STATES

DESIGNATED/ELECTED OFFICE (DO/EO/US)

CONCERNING A FILING UNDER 35 U.S.C. 371

RCA90121

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR

09/509969

INTERNATIONAL APPLICATION NO.

PCT/FR98/02240

INTERNATIONAL FILING DATE

19 OCTOBER 1998

PRIORITY DATE CLAIMED

17 OCTOBER 1997

TITLE OF INVENTION

CONTROL DEVICE AND METHOD IN A HOME NETWORK

APPLICANT(S) FOR DO/EO/US

FABIEN BATTINI and BENOIT GUERIN

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This is an express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371 (c) (2))
 - a. ☐ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☒ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☒ A copy of the International Search Report (PCT/ISA/210).
8. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☒ have not been made and will not be made.
9. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
10. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)).
11. ☒ A copy of the International Preliminary Examination Report (PCT/IPEA/409).
12. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)).

Items 13 to 20 below concern document(s) or information included:

13. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
14. ☒ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
15. ☐ A **FIRST** preliminary amendment.
16. ☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
17. ☐ A substitute specification.
18. ☐ A change of power of attorney and/or address letter.
19. ☒ Certificate of Mailing by Express Mail
20. ☐ Other items or information:

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR 09/509969	INTERNATIONAL APPLICATION NO. PCT/FR98/02240	ATTORNEY'S DOCKET NUMBER RCA90121
--	--	---

21. The following fees are submitted:.				CALCULATIONS PTO USE ONLY	
BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)) :					
<input type="checkbox"/> Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO				\$970.00	
<input checked="" type="checkbox"/> International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO				\$840.00	
<input type="checkbox"/> International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO				\$690.00	
<input type="checkbox"/> International preliminary examination fee paid to USPTO (37 CFR 1.482) but all claims did not satisfy provisions of PCT Article 33(1)-(4)				\$670.00	
<input type="checkbox"/> International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(1)-(4)				\$96.00	
ENTER APPROPRIATE BASIC FEE AMOUNT =				\$840.00	
Surcharge of \$130.00 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492 (e)).				\$0.00	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE		
Total claims	8 - 20 =	0	x \$18.00	\$0.00	
Independent claims	2 - 3 =	0	x \$78.00	\$0.00	
Multiple Dependent Claims (check if applicable).			<input type="checkbox"/>	\$0.00	
TOTAL OF ABOVE CALCULATIONS =				\$840.00	
Reduction of 1/2 for filing by small entity, if applicable. Verified Small Entity Statement must also be filed (Note 37 CFR 1.9, 1.27, 1.28) (check if applicable).				<input type="checkbox"/>	\$0.00
SUBTOTAL =				\$840.00	
Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492 (f)).				\$0.00	
TOTAL NATIONAL FEE =				\$840.00	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31) (check if applicable).				<input type="checkbox"/>	\$0.00
TOTAL FEES ENCLOSED =				\$840.00	
				Amount to be: refunded	\$
				charged	\$

☐ A check in the amount of _____ to cover the above fees is enclosed.


☒ Please charge my Deposit Account No. **07-0832** in the amount of _____ to cover the above fees.
A duplicate copy of this sheet is enclosed.

☒ The Commissioner is hereby authorized to charge any fees which may be required, or credit any overpayment to Deposit Account No. **07-0832** A duplicate copy of this sheet is enclosed.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

JOSEPH S. TRIPOLI - PATENT OPERATIONS
THOMSON MULTIMEDIA LICENSING, INC.
PO BOX 5312 - 2 INDEPENDENCE WAY
PRINCETON, NJ 08543-5312


SIGNATURE

David T. Shoneman
NAME

39,371
REGISTRATION NUMBER

4/5/00
DATE

527 Rec'd PCT/PTO 03 APR 2000

Control device and method in a home networkFIELD OF THE INVENTION

5

The invention relates to a control device and method in a domestic-appliance network.

Domestic appliance should be understood as meaning at least one domestic appliance, such as a video and/or audio appliance (for example, a television set, a tape recorder, a hi-fi system, etc.) and/or at least one electrical appliance (for example, a microwave oven, a refrigerator, a circuit breaker, etc.)

Control of a domestic appliance should be understood as meaning the management of various items of information, such as information allowing the appliance to be set, information relating to the appliance's current operation, information relating to the technical characteristics of the appliance or else safety guidelines which are to be observed.

DESCRIPTION OF RELATED ART

According to the prior art, the information relating to setting, the technical characteristics and the safety guidelines for an appliance is contained in the printed booklet constituting the appliance's instructions. Once this information is known, the user sets the appliance by making adjustments to the appliance itself either directly or, in certain cases, using a remote control.

The information relating to the current operation of an appliance is displayed on the front of the appliance. As non-limiting examples, the front of a compact disc player displays the number of the disc's track number currently being played, or a microwave oven displays the power to which it has been set.

A domestic appliance is thus controlled on the basis of a variety of information which the user employs when making multiple adjustments.

When a user wishes to operate a plurality of domestic appliances simultaneously, he thus has to make adjustments to each of them. The number of operations which the user needs to carry out is thus greatly increased, and this very fact results in real drawbacks. Thus, for example, a user wishing to record a television programme received by a first appliance on a second appliance needs to program each of the appliances separately.

The invention does not have these drawbacks.

15

BRIEF SUMMARY OF THE INVENTION

Specifically, the invention relates to a control device in a domestic-appliance network, wherein each appliance has an associated descriptor comprising a set of HTML pages or page parts for controlling said appliance, said device having

- means for loading and processing descriptors associated with the appliances,
- means for displaying HTML pages or page parts for the descriptors loaded, a descriptor comprising configuration data which identifies an appliance as a source and/or a receiver of a data type, said control device using configuration data for a plurality of appliances to create at least one configuration page in order to allow the user to specify the connections between appliances.

According to one particular illustrative embodiment, the display means comprise a television set. These means can also comprise a video monitor, an LCD or plasma screen, a display of the light-emitting-diode type or another type of display.

According to one particular example, an IEEE 1394 interface, the loading and processing means comprise a microprocessor and a memory. However,

depending on the design, in particular depending on the type of communication bus in the network, the interface can be different and, in particular, wireless. Furthermore, the microprocessor can be replaced by a
5 microcontroller or another type of data-processing device. Similarly, the memory can be of the random access memory or programmable read-only memory type, depending on the type of use envisaged.

According to one particular aspect of the
10 invention, the control device analyses the descriptors obtained to determine similar functions in these descriptors, for example audio volume settings, and creates HTML pages which combine these functions. This characteristic is patentable per se.

15 One advantage of the invention is that it allows various appliances operating at the same time to be controlled centrally.

BRIEF DESCRIPTION OF THE DRAWINGS

20 Other features and advantages of the invention will become apparent on studying embodiments of the invention with reference to the appended figures, in which:

25 - Figure 1 shows a system for controlling domestic equipment using a graphical screen display according to a first embodiment of the invention;

- Figure 2 shows a detailed view of a specific item of domestic equipment according to the invention;

30 - Figure 3 shows a system for controlling domestic equipment using a graphical screen display according to a second embodiment of the invention, and

- Figure 4 shows an improvement to the systems shown in Figures 1 and 3.

35 In all the figures, the same reference symbols denote the same elements.

DETAILED DESCRIPTION OF THE INVENTION

Figure 1 shows a system for controlling domestic equipment using a graphical screen display according to a first embodiment of the invention.

5 The system shown in Figure 1 comprises n items of domestic equipment EQ1, EQ2, ..., EQn, n being an integer greater than or equal to 1.

Each item of domestic equipment (EQj (j = 1, 2, ..., n) is connected to an interface Ij. According to a first embodiment of the invention, the item of domestic equipment EQj and the interface Ij are independent devices connected to one another by means of a connection. According to a second embodiment of the invention, the interface Ij is integrated in the item of domestic equipment EQj in such a manner that all
10 that is formed is a single appliance.
15

The various interfaces Ij are connected to one another and to a control device CTR by means of an electrical network B. The control device CTR is connected to a display device D. According to the preferred embodiment of the invention, the electrical network B is a data bus, such as the bus defined by IEEE standard 1394.
20

The display device D may be, for example, a television set or else a computer of the PC (personal computer) type.
25

For each item of domestic equipment, the information which can be displayed on the screen of the device D is, for example, all or some of the information listed below:

30 - Information allowing the item of domestic equipment to be set and operated. This information can vary from one moment to the next at a greater or lesser rate. It is obtained from instantaneous measurements carried out, for example at regular intervals of time, on the appliance which is operating. For example, it
35 may be information giving the remaining playing time on a track of an audio compact disc or else information giving the temperature of an electric oven.

5

10

15

20

25

30

35

of domestic equipment with which the interface I_j is associated.

Thus, another advantage of the invention is that it proposes an electronic means for storing,
5 retrieving and displaying information relating to the domestic equipment.

As mentioned above, the electronic form held in an interface I_j ($j = 1, 2, \dots, n$) is made up of computer data and of means allowing this computer data
10 to be stored and communicated.

The means allowing the computer data to be stored and communicated can be formed merely by memory circuits containing the data. They can also be formed by memory circuits and a microprocessor for more
15 complex applications, such as the creation of documents resulting from a program being executed.

All or some of the computer data is made up of the following data:

- A set of pages and/or page parts using the
20 mark-up language used for creating documents within the hypermedia system commonly called the worldwide web. This mark-up language will subsequently be called HTML (Hyper Text Mark-up Language). These pages thus contain the static information relating to the appliance, that
25 is to say data which does not change over time, and programs allowing this data to be accessed, such as programs known as Java programs and JavaScript programs.

- A set of declarations, or meta-information,
30 allowing all or some of the page parts to be aggregated using the control device CTR. For example, the descriptors for a plurality of appliances can each comprise a volume setting function, which is identified by a particular function type. The controller CTR can
35 thus set up a single page of information containing all the audio volume settings for the appliances in question, by recognizing the function type in the descriptors.

- A set of programs allowing dynamic pages to be created or allowing dynamic information to be retrieved. As an example, these may be programs known on the worldwide web, such as the Java program, the JavaScript program, or else the CGI (Common Gateway Interface) program.

The number of computer tools which are compatible with HTML is very large. Advantageously, it follows that the description of the pages and page parts utilizing HTML can be designed using a great variety of computer tools. As an example, when information is shown in the form of images, the standards commonly called GIF, JPEG or else MPEG can be used for coding the information. The acronyms GIF, JPEG and MPEG stand for «Graphic Interchange Format», «Joint Photographic Expert Group» and «Moving Picture Expert Group», respectively.

The device CTR is, for example, a digital decoder equipped with an IEEE 1394 interface (reference 10 in Figure 1) connecting it to the communication bus. The decoder is provided with a microprocessor 11 and with a memory 12 for loading, processing and storing the descriptors and the programs which it contains. The microprocessor, the bus interface and the memory are connected to an internal bus 13. The decoder also has a character generator 14 for generating the graphics necessary for displaying the user interfaces and the information.

The descriptor held in the interface Ij is communicated to the control device CTR by means of the network B. As mentioned above, in accordance with the preferred embodiment of the invention, the network B is a data bus, such as the bus defined by IEEE standard 1394.

According to a first embodiment of the invention, the phase of communicating all or some of the descriptor held in an interface Ij to the control device CTR takes place as soon as the interface Ij has been connected to the control device CTR. As an

example, when the data bus defined by IEEE standard 1394 is used, this communication phase can be implemented during the automatic data interchange protocol which takes place when the interface Ij is
5 connected to the bus.

According to another embodiment of the invention, the phase of communicating all or some of the descriptor held in the interface Ij takes place at the request of the control device CTR and may be carried
10 out several times on the basis of the same protocol, should this prove to be necessary.

The descriptor held in an interface Ij can be communicated by the communication protocol used for data interchanges between clients and servers on the
15 worldwide web. This communication protocol will subsequently be called HTTP (Hyper Text Transfer Protocol). According to the invention, however, other communication protocols may be used. For example, the phase of connecting an appliance to the IEEE 1394 bus
20 has a data interchange phase which can be used to this end.

With the hypermedia system commonly called the worldwide web, the HTTP uses the services of a protocol stack commonly called the TCP/IP stack (the acronym
25 TCP/IP stands for «Transmission Control Protocol/Internet Protocol»). The TCP/IP stack is relatively costly to install. One advantage of the invention is that it allows the use of protocols other than those of the TCP/IP stack to support the HTTP.

When all or some of the descriptor is communicated from an interface Ij to the control device CTR, the latter inserts pages and/or page parts in HTML into its tree structure. The «tree structure» of the control device should be understood as meaning the set
30 of pages which the control device allows to be linked to one another and displayed as a result of a graphics or text symbol being activated.

Each page in HTML is identified by an address. According to a first embodiment of the invention, among

the pages in HTML which are inserted into the tree structure of the control device there is at least one header page containing the list of the addresses of the various pages. When consulted, this header page allows
5 any HTML page to be retrieved using the address of the HTML page.

According to another embodiment of the invention, it is also possible to insert into the tree structure of the control device an HTML page assembling
10 a list of pointers, with each pointer corresponding to an address for an HTML page describing the appliance. When consulted, the HTML page assembling the list of pointers thus allows any HTML page to be retrieved using the pointer corresponding to the address of the
15 page.

Advantageously, the HTML page containing the list of the addresses or the HTML page assembling the list of the pointers provide the user with easy access to the various information relating to the appliances
20 used. Furthermore, these HTML pages can be easily modified. It is thus possible to update them, without any difficulty, when a new appliance is connected to the network B.

It is also possible, according to the invention, to create a page listing the appliances connected to the network B. A graphics object formed by a line of text and/or by a drawing can thus be used to indicate the presence of an appliance, which is equivalent to its descriptor being inserted into the
25 tree structure of the control device. This graphics object can be used to direct the user towards new specific pages relating to the appliance. This page is advantageously created by the control device on the basis of the set of descriptors loaded from the
30 appliances.
35

The use of HTML has the advantage of allowing the user to choose how to show the information which he wishes to display. Thus, for example, this manner of showing information may be made consistent for the same

kind of information, such as information relating to the audio level of various appliances or information relating to the power consumed by various appliances.

According to an improvement to the embodiment of the invention, an interface Ij can contain a set of declarations allowing the appliance which is associated with it to be configured as a source and/or as a receiver of data, such as audio and/or video data.

The control device CTR then comprises means for creating configuration pages allowing a declaration to be made of which appliance is being used and what its function is (transmitter for a first signal (audio, video, etc.) or data list or receiver for a second list) as well as pages suggesting the possible connections between various appliances or providing the user with a means allowing him to specify the connection or connections which he wishes to set up between various appliances.

As a non-limiting example, a television set can be declared as being an audio transmitter and a hi-fi system can be declared as being an audio receiver. The descriptor for the television set then has a declaration to the effect that the appliance can be an audio source (and also a video signal source, an audio receiver and a video signal receiver, etc.). The control device CTR can then construct a configuration page describing this situation.

When a control unit, such as a remote control, is used, the control device CTR advantageously allows all of the domestic appliances connected to the network B to be controlled.

Control is initiated, in a manner known per se, by the user interacting with a graphics object (text and/or symbol) displayed on the screen of the device D.

This interaction is converted into a command by a command program stored in a memory circuit held in the control device. According to the preferred embodiment of the invention, the command program's language is the Java language, for example. According

to other embodiments of the invention, it can also be a command language other than one of the command languages known on the worldwide web. Thus, for example, it may be an extension of HTML. Extension of
5 HTML should be understood as meaning the addition to the HTML of certain keywords whose use syntax conforms to the usual syntax of the HTML.

According to the present embodiment, the following syntax is defined for specifying a volume
10 setting function:

```
<COMMAND MIN=0, MAX=100, DELTA=1, LABEL=  
'Volume', PROTOCOL='AV/CTS', IDENT='MY IDENTIFIER'>
```

where 'COMMAND' denotes the function type, namely a command, MIN and MAX define the minimum and
15 maximum setting values, respectively, DELTA defines the increment, LABEL defines the name to be given to the function, PROTOCOL defines the protocol used to control the appliance in question and IDENT defines an identifier for the appliance calling the function.

20 Furthermore, the JavaScript language can be used to write the user interaction program.

Using an extension of HTML to cover all or some of the setting commands for the appliances connected to the network B advantageously allows the symbols
25 representing the same kind of commands to be made consistent. This simplifies the control of different appliances.

Initially, the command program for a domestic appliance is held in the interface which is associated
30 with it. When the descriptor is communicated to the control device CTR, the command program is loaded into the control device, which is then able to execute it.

Figure 2 shows a detailed view of a particular item of domestic equipment according to the invention.

35 The element shown in Figure 2 is made up of an item of domestic equipment EQi and an interface Ii associated with the item of domestic equipment EQi.

As a non-limiting example, the item of domestic equipment EQi comprises three electrical appliances 1,

2, 3, such as those mentioned previously. In a more general way, however, the item of domestic equipment EQi comprises at least one electrical appliance.

5 The electrical appliances 1, 2, 3 are connected to the interface Ii by means of an electrical network b. The electrical network b can be made up of a set of electrical wires, for example.

10 The interface Ii contains all of the descriptors for the appliances 1, 2, 3 as well as various circuits allowing the data passed over the network B to be converted into quantities which are compatible with the electrical appliances.

15 Figure 3 shows a system for controlling domestic equipment using a graphical screen display according to a second embodiment of the invention.

In addition to the elements listed in Figure 1, the control system shown in Figure 3 comprises an item of domestic equipment EQy and an interface Iy.

20 The item of domestic equipment EQy is formed by at least one electrical appliance, such as those mentioned above. The interface Iy contains all of the descriptors for the electrical appliances forming the item of domestic equipment EQy.

25 The interface Iy is then connected directly to the control device CTR by electrical wires. According to this embodiment of the invention, the information interchanged between the electrical appliances forming the item of equipment EQy and the control device CTR is no longer passed over the network B.

30 This embodiment can be particularly advantageous for certain particularly simple electrical appliances, such as circuit breakers, because it is then not necessary to convert simple electrical quantities, such as a voltage value or a current value, into data which is compatible with the network B.

35 According to a particular embodiment, the interface Iy and the control device CTR can then be integrated into a single device DI.

Figure 4 shows an improvement to the system shown in Figures 1 and 3.

In addition to the elements described in Figure 1, the system shown in Figure 4 comprises a
5 modem MD which is connected, on the one hand, to the bus B and, on the other hand, to a network R which is external to the set formed by the domestic equipment EQj, the interfaces Ij, the network B, the control device CTR and the display device D. The network R may
10 be a telephone network, for example.

According to the preferred embodiment of the improvement shown in Figure 4, all or some of the descriptor for at least one item of domestic equipment is communicated by means of a reference commonly used
15 on the worldwide web to specify the physical location of a file or resource. This reference will subsequently be called the URL (Uniform Resource Locator).

The control device can then go and retrieve the required document from the indicated location via the
20 modem MD and the network R using the URL. During this operation, various protocols may be used, such as HTTP, BOOTP, FTP and TFTP. The acronyms BOOTP, FTP and TFTP stand for «Boot Protocol», «File Transfer Protocol» and «Trivial File Transfer Protocol», respectively.

25 HTTP is a relatively costly protocol. Advantageously, it is not imperative for the descriptor communication phase, as mentioned above, to be carried out on the basis of HTTP.

Another advantage of the embodiment shown in
30 Figure 4 is the updating of the information in one or more descriptors for domestic equipment using the modem MD connected to the network R. Advantageously, new information relating to the domestic equipment can thus be made accessible to the user. This updating function
35 is particularly useful, for example, in the case of commercial information such as that mentioned above, or else in the case of information relating to the safety of the appliance.

The modem shown in Figure 4 is a device in itself, separate from the other equipment. The invention also relates to other configurations, such as those in which the modem is contained in a telephone
5 answering machine or in a terminal which allows access to the hypermedia system formed by the worldwide web.

CLAIMS

1. Control device (CTR) in a home network, wherein each appliance has an associated descriptor comprising
5 a set of HTML pages or page parts for controlling said appliance, said device having

- means for loading and processing descriptors associated with the appliances,

- means (D) for displaying HTML pages or page
10 parts for the descriptors loaded, a descriptor containing configuration data which identifies an appliance as a source and/or a receiver of a data type, said control device using configuration data for a plurality of appliances to create at least one
15 configuration page in order to allow the user to specify the connections between appliances.

2. Device according to Claim 1, wherein a descriptor is loaded directly from the appliance with which it is associated, said descriptor being stored in
20 a memory in this appliance.

3. Device according to Claim 1, wherein a descriptor is loaded from an Internet server, the address of the descriptor being loaded from the appliance with which the descriptor is associated.

25 4. Device according to Claim 1, further comprising means for aggregating functions of the same type for a plurality of descriptors in order to display aggregated functions on a single page or in order to aggregate a plurality of page parts to display aggregated page
30 parts on a single page.

5. Device according to Claim 1, wherein a descriptor contains at least one of the following functions: display of static information relating to the appliance, display of dynamic information relating
35 to the appliance, display of an object for controlling a function of the appliance.

6. Device according to Claim 5, wherein, when a descriptor contains an object for controlling a function of an appliance, it also contains a program

for generating the corresponding command to be transmitted to the appliance with which the set is associated.

7. Device according to Claim 1, wherein the at
5 least one configuration page indicates all the possible configurations.

8. Method of controlling at least one appliance in a domestic communication network having a control device connected to a display device, comprising the
10 steps:

- of loading, using said control device, descriptors comprising a set of HTML pages or page parts for controlling at least one appliance associated with the descriptors, said descriptors containing
15 configuration data which identifies an appliance as a source and/or a receiver of a data type,

- of creating, using said control device, at least one configuration page from the configuration data for a plurality of appliances in order to allow
20 the user to specify the connections between appliances.

ABSTRACT

Control device (CTR) in a domestic-appliance network, in which each appliance has an associated descriptor comprising a set of HTML pages or page parts for controlling said appliance.

The device has

- means for loading and processing descriptors associated with the appliances,

- means (D) for displaying HTML pages or page parts for the descriptors loaded, a descriptor containing configuration data which identifies an appliance as a source and/or a receiver of a data type, said control device using configuration data for a plurality of appliances to create at least one configuration page in order to allow the user to specify the connections between appliances.

The invention also relates to a control method in a domestic-appliance network.

The invention applies, in particular, to home networks.

Figure 1




FIG.1




FIG. 2




FIG.3




FIG.4

CONTROL DEVICE AND METHOD IN A HOME NETWORK

29 boulevard Volney
F-35700 Rennes
France